

HeartSine® samaritan® PAD 500P AED

Automated external defibrillator with integrated
CPR Advisor™

Data sheet

Key link in the chain of survival

Cardiopulmonary Resuscitation (CPR) and automated external defibrillators (AEDs) are key links in the chain of survival of sudden cardiac arrest (SCA). Some cardiac events are treatable with effective CPR alone. Others require a combination of effective CPR and the delivery a lifesaving shock by an AED. Either way, every minute counts.¹

Only about five percent of SCA victims survive.² However, survival rates can increase up to 74%³ if CPR and a shock from an AED are provided within three minutes of collapse. Reducing response time by even one or two minutes from collapse to shock can mean the difference between death and survival.¹

Offering real-time CPR feedback, the HeartSine samaritan PAD 500P (SAM 500P) automated external defibrillator (AED) with CPR Advisor meets the needs of two key links in the chain of survival. Not only can the SAM 500P deliver a lifesaving shock, it provides real-time visual and verbal feedback to the rescuer on the force and rate of CPR compressions during an SCA resuscitation — effectively assisting the rescuer to perform CPR.



Real-time CPR feedback



Integrated real-time CPR feedback

Easy-to-understand visual and voice prompts guide the rescuer through the entire resuscitation process, providing specific feedback on the force and rate of compressions.

Ready to shock



Unique Pediatric-Pak

Ensures the guidelines-recommended energy level is delivered for children, between 1 and 8 years of age or up to 25 kg (55 lb).



High level of protection from dust and water

Offers IP56 rating, one of the highest ratings in the industry.



Clinically validated technology⁴

Advanced electrode technology and SCOPE biphasic technology, a low energy escalating waveform that automatically adjusts for differences in patient impedance.



Highly portable

With the lightest weight and most compact footprint among leading AEDs, is easily transported and fits into constrained spaces.

Simple to own



Two parts, one expiration date

The innovative Pad-Pak, an integrated battery and electrode single-use cartridge with one expiration date, offers one simple maintenance change every four years.




Low cost of ownership

Shelf life of four years means that the Pad-Pak may offer savings over other defibrillators that require separate battery and electrode replacements.



8-year warranty

AED is backed by an 8-year limited warranty.



Specifications

Defibrillator

Waveform: Self-Compensating Output Pulse Envelope (SCOPE) optimized biphasic escalating waveform compensates energy, slope and duration for patient impedance

Patient analysis system

Method: Evaluates patient's ECG, electrode contact integrity and patient impedance to determine if defibrillation is required

Sensitivity/Specificity: Meets IEC/EN 60601-2-4

Impedance range: 20-230 ohms

Energy selection

Pad-Pak:

Shock 1: 150 J

Shock 2: 150 J

Shock 3: 200 J

Pediatric-Pak:

Shock 1: 50 J

Shock 2: 50 J

Shock 3: 50 J

Charge time (typical):

150 J in < 8 seconds

200 J in < 12 seconds

Environmental

Operating/Standby temperature:

0°C to 50°C (32°F to 122°F)

Transport temperature:

0°C to 50°C (32°F to 122°F)

NOTE: It is recommended that the device should be placed in an ambient temperature of between 0°C to 50°C (32°F to 122°F) for at least 24 hours upon first receipt

Relative humidity: 5% to 95% non-condensing

Water resistance: IEC 60529/ EN60529 IPX6 with electrodes connected and battery installed

Dust resistance: IEC 60529/ EN60529 IP5X with electrodes connected and battery installed

Enclosure: IEC/EN 60529 IP56

Altitude: -381 to 4 575 meters (-1,250 to 15,000 feet)

Shock: MIL STD 810F Method 516.5, Procedure 1 (40 G's)

Vibration: MIL STD 810F Method 514.5, Procedure 1
Category 4 Truck Transportation – US Highways

Category 7
Aircraft – Jet 737 & General Aviation

Atmospheric pressure: 572 hPa to 1060 hPa (429 mmHg to 795 mmHg)

EMC: IEC/EN 60601-1-2

Radiated emissions: IEC/EN 55011

Electrostatic discharge:

IEC/EN 61000-4-2 (8 kV)

RF immunity:

IEC/EN 61000-4-3 80MHz-2.5 GHz, (10 V/m)

Magnetic field immunity:

IEC/EN 61000-4-8 (3 A/m)

Aircraft: RTCA/DO-160G, Section 21 (Category M)

RTCA/DO-227 (ETSO-C142a)

Falling height: 1 meter (3.3 feet)

Physical characteristics

With Pad-Pak inserted:

Size:

20 cm x 18.4 cm x 4.8 cm
(8.0 in x 7.25 in x 1.9 in)

Weight: 1.1 kg (2.4 lb)

Accessories

Pad-Pak Electrode and Battery Cartridge

Shelf life/Standby life: See the expiration date on the Pad-Pak/Pediatric-Pak (4 years from manufacture date)

Weight: 0.2 kg (0.44 lb)

Size:

10 cm x 13.3 cm x 2.4 cm
(3.93 in x 5.24 in x 0.94 in)

Battery type: Disposable single-use combined battery and defibrillation electrode cartridge (lithium manganese dioxide (LiMnO₂) 18V)

Battery capacity (new):

> 60 shocks at 200 J or 6 hours of battery use

Electrodes: Disposable defibrillation pads are supplied as standard with each device

Electrode placement: Anterior - lateral (Adult)

Anterior - posterior or Anterior - lateral (Pediatric)

Electrode active area: 100 cm² (15 in²)

Electrode cable length: 1 meter (3.3 feet)

Aircraft safety test (TSO/ETSO-certified Pad-Pak): RTCA/DO-227 (ETSO-C142a)

Data storage

Memory type: Internal memory

Memory storage: 90 minutes of ECG (full disclosure) and event/incident recording

Review: Custom USB data cable (optional) directly connected to PC with Saver EVO Windows-based data review software

Materials used

Defibrillator housing: ABS, Santoprene

Electrodes: Hydrogel, Silver, Aluminium and Polyester

Warranty

AED: 8-year limited warranty

References

1. Mosesso Jr VN, et al. 2002. Proceedings of the National Center for Early Defibrillation Police AED Issues Forum. *Prehospital Emergency Care*. 6(3):273–82.
2. Mehra R. Global public health problem of sudden cardiac death. *Journal of Electrocardiology*. 2007;40(6):S118-S122.
3. Valenzuela TD, et al. 2000. Outcomes of Rapid Defibrillation by Security Officers After Cardiac Arrest in Casinos. *New England Journal of Medicine*. 343:1206-09.
4. Walsh SJ, McClelland A, Owens CG, et al. Efficacy of distinct energy delivery protocols comparing two biphasic defibrillators for cardiac arrest. *Am J Cardiol*. 2004;94:378–380.

All claims valid as of 03/2022.

For further information, please contact Stryker at 800 668 8323 (Canada) or visit our website at strykeremergencycare.com

Emergency Care Public Access

AED users should be trained in CPR and in the use of the AED.

Although not everyone can be saved, studies show that early defibrillation can dramatically improve survival rates. AEDs are indicated for use on adults and children. AEDs may be used on children weighing less than 25 kg (55 lb) but some models require separate defibrillation electrodes.

The information presented is intended to demonstrate Stryker's product offerings. Refer to operating instructions for complete directions for use indications, contraindications, warnings, cautions, and potential adverse events, before using any of Stryker's products. Products may not be available in all markets because product availability is subject to the regulatory and/or medical practices in individual markets. Please contact your representative if you have questions about the availability of Stryker's products in your area. Specifications subject to change without notice.

Stryker or its affiliated entities own, use, or have applied for the following trademarks or service marks: CPR Advisor, HeartSine, Pad-Pak, Pediatric-Pak, samaritan, Saver EVO, SCOPE, Stryker. All other trademarks are trademarks of their respective owners or holders.

The absence of a product, feature, or service name, or logo from this list does not constitute a waiver of Stryker's trademark or other intellectual property rights concerning that name or logo.

 0123 HeartSine samaritan PAD; Pad-Pak; Pediatric-Pak

 HeartSine Gateway

 vs HeartSine samaritan PAD: UL Classified. See complete marking on product.

Date of Issue: 03/2022

Made in U.K.

H009-014-036-AB EN-CN

HeartSine SAM 500P is not available for sale in the U.S.

Copyright © 2022 Stryker.



Manufactured by:

HeartSine Technologies, Ltd.
207 Airport Road West
Belfast
Northern Ireland
BT3 9ED
United Kingdom
Tel +44 28 9093 9400
Fax +44 28 9093 9401
heartsinesupport@stryker.com
heartsine.com

Distributed in Canada by:

Stryker Canada
2 Medicorum Place
Waterdown, Ontario
L8B 1W2
Canada
Toll free 800 668 8323